

TECHNICAL DATA

CHAMP PRO BATTERY CHARGERS

STATED DATA ACCORDING TO MICROPOWER STANDARD

Part number	0043890
Model	Champ Pro
Type	12V/30A

MAINS DATA (50/60HZ)

Output Voltage [V]	12
Output Current [A]	30
Number of phases	1
Rated Voltage range [V]	190-254
Current at nominal voltage [A]	
Recommended supply fuse [A]	
Supply cable area	3×1,0mm ²
Supply cable length [m]	1.5m
Typical Supply Connector	
Output cable cross-section	6mm ² , 1,5m

BATTERY CONNECTION

Output cable cross-section	6mm ² , 1,5m
Output cable terminals (in unit)	
Output cable length [m]	
Typical Output connector	
Output Voltage [V]	12

ELECTRIC DATA

Standby Power Consumption [W]	
Power Consumption [W]	
Apparent Power Consumption [VA]	

Power Factor

Inrush current, do not tripp fuse of class [A]

Output Ripple

Efficiency (at rated power and no cables) [%]

PROPERTIES

Ingress protection IP67

Ambient temperature range (at full output power) [deg C]

Ambient max temp (with reduced output power) [deg C]

Cooling: 1=Fan, 2= Convection

Short Circuit Protection No

Wrong Polarity Protection

Cabinet Type

Certifications

HMI

HMI Language

Reporting No

Radio Communication No

Charging Curve Set

I/O-cards

CE No

UL No

CHARGING TIMES

6 Hours cap.ah/5h

8 Hours cap.ah/5h

10 Hours cap.ah/5h

12 Hours cap.ah/5h

CHARGER DIMENSIONS

Weight excl. cables [kg]

Weight incl. cables [kg]

Outer Dimensions Height [mm]

Outer Dimensions Width [mm]

Outer Dimensions Depth [mm]

Min Spacing Required

SHIPPING DIMENSIONS

Shipping Weight [kg]

Box Height [mm]

Box Width [mm]

Box Depth [mm]

CHARGING

Charging Ionic

Charging Standard

Charging Gel

Charging Li-Ion

Charging AGM

Moisture Resistance No

Dusty Environment No

Outdoor use No

Cold store No

Tropical No

The information in this document is subject to change without notice and should not be construed as a commitment by Micropower E.D. Marketing AB.